

Proxima Pro AV 9350 Projector

Technical and Functional Specifications

Native Resolution	<ul style="list-style-type: none">● XGA (1024 x 768)
Resolutions Supported	<ul style="list-style-type: none">● XGA (1024x768); Fit-to-View display of VGA (640 x 480), SVGA (800 x 600), SXGA (1280 x 1024)
Brightness	<ul style="list-style-type: none">● 5000 ANSI lumens
Brightness Uniformity	<ul style="list-style-type: none">● 85%
Contrast Ratio	<ul style="list-style-type: none">● 700:1 (full on/full off)
Computer Compatibility	<ul style="list-style-type: none">● IBM PC, PS/2, Pentium and Compatibles● SUN, SGI, IBM, HP, DEC● Apple Macintosh, Power Macintosh, PowerBook
Video Compatibility	<ul style="list-style-type: none">● PAL, SECAM, NTSC, NTSC 4.43, PAL-M,PAL-N● HDTV (480i, 480p, 575i, 575p, 720p, 1035i, 1080i-50,1080i-60)
Display Technology	<ul style="list-style-type: none">● 1.8 in. polysilicon TFT LCD x 3 with micro lens array
Number of Colors	<ul style="list-style-type: none">● 16.7 million
Input Sources	<ul style="list-style-type: none">● DVI-I, audio, control (DIN-8); BNC x 5 (R/Pr, G/y, B/Pb, H/HV, V) audio, control (DIN-8); BNC x 2 (Video/Y,C) audio, S-Video; D-Sub15, audio, control (DIN-8); Serial Port in (DB-9); USB
Output	<ul style="list-style-type: none">● Serial Out, Audio Out
H-Sync Range	<ul style="list-style-type: none">● 15-120 kHz
V-Sync Range	<ul style="list-style-type: none">● 50-120 Hz
Horizontal Resolution	<ul style="list-style-type: none">● 700 TV Lines
Lens Shift	<ul style="list-style-type: none">● Up, down, left and right
Digital Keystone Correction	<ul style="list-style-type: none">● +/-30 degrees
Projection Lens	<ul style="list-style-type: none">● Std. Lens - power zoom and focus,F 2.0~2.3, f 75.7 mm to 97.5 mm
Projection Distance/Image Width	<ul style="list-style-type: none">● 2.0 - 2.6:1
Projection Distance	<ul style="list-style-type: none">● 5.4 ft. to 104 ft. (1.6 m to 31.7 m)
Zoom	<ul style="list-style-type: none">● 1.3:1
Aspect Ratio	<ul style="list-style-type: none">● Std: 4:3, supports 16:9, 5:4
Image Size (Diagonal)	<ul style="list-style-type: none">● 3.3 ft. to 50 ft. (1 m to 15.2 m)
Projection Method	<ul style="list-style-type: none">● Front, rear, ceiling, desk
Remote Control	<ul style="list-style-type: none">● Wired/Wireless IR remote with mouse control and laser pointer
Lamp (Life)	<ul style="list-style-type: none">● 150 W UHP x 4 (1,500 hours normal; 3,000 hours low bright)
Weight	<ul style="list-style-type: none">● 78.4 lbs. (35.5 kg.)
Dimensions (W x H x L)	<ul style="list-style-type: none">● 22.9 x 9.9 x 31.2 in. (58.1 x 25.2 x 79.2 cm)
Power Consumption	<ul style="list-style-type: none">● 1000 W
Power Requirements	<ul style="list-style-type: none">● 100 to 120V / 200 to 240V 50/60Hz
Operating Temperature	<ul style="list-style-type: none">● 41° F - 95° F (5° C to 35° C)
On-Screen Menu Languages	<ul style="list-style-type: none">● English, German, French, Italian, Spanish, Japanese
Audible Noise	<ul style="list-style-type: none">● <45dB

Approvals

- FCC Class A, UL, c-UL, CE

Warranty

- Two years parts and labor (excluding the lamp)
- 90-day (or 500 hours) limited lamp warranty